

Wed1.5

Schwaederlé et al.

Measurements of turbulent mixing within an air/SF₆ shocked and reshocked interface**Laurent Schwaederlé, Jean-François Haas, Philippe Montlaurent, Claude Rayer & Guillaume Seguin**

Commissariat à l'Énergie Atomique,
Bruyères le Châtel, France
jean-francois.haas@cea.fr

We observe in a vertical shock tube the behaviour of an air/SF₆ mixing zone induced by the Richtmyer-Meshkov instability and excited by two subsequent waves reflected from the upper end wall: a shock and a rarefaction. The 1 m long driver and 3.058 m long driven sections are filled with air, and are followed by the 250 or 300 mm long measurement section filled with SF₆, at local atmospheric pressure (1 bar). The nominal Mach numbers are 1.20, 1.06, 1.304 and 1.297 for the incident, reflected in air (from the interface), the transmitted into SF₆ and reflected in SF₆ (from the end wall) shock waves respectively. Here, the shock wave propagates upwards from air into SF₆. The discontinuous interface between the test gases air and SF₆, which after shock acceleration leads to the mixing zone, is materialized by a thin (0.5 μm) nitrocellulose film sandwiched between two stainless steel wire grids. The upper (respectively lower) grid has a wire spacing of 1.8 (1.0) mm, with a wire diameter of 0.23 (0.07) mm. The lower grid is needed to support the membrane. The role of the upper grid is to impose a non-linear three dimensional perturbation of fundamental wave length 1.8 mm in the transverse directions. The perturbation amplitude in the axial direction is estimated between 0.1 and 0.3 mm. This wavelength and amplitude combination leads to an early transition to turbulence. After incident shock (reflected shock) the mixing zone moves upwards (downwards) at 69.4 (-24.7) m/s with an Atwood of 0.70 (-0.72). We measure the mixing thickness and velocity variance evolution for comparison with calculated quantities from turbulent mixing models imbedded in one-dimensional hydrodynamic codes [1]. The mixing thickness evolutions obtained from Schlieren visualisation for two initial SF₆ lengths (300 and 250 mm) exhibit power law dependence on time with exponent θ equal to 0.23 ± 0.05 before reshock, 0.60 ± 0.32 and 0.83 ± 0.15 after reshock, for 250 mm and 300 mm respectively. The measurements of the axial and transversal components of the velocity will be performed for 250 mm using a DANTEC two components laser doppler velocimeter [2] at the three axial locations: 30, 88 and 146 mm.

References

- [1] D. Souffland et al. 1997 Measurements and Simulations of the Turbulent Energy Levels in Mixing Zones Generated in Shock Tubes, Proceeding of the 6th IWPCTM, Marseille, June 1997, G. Jourdan and L. Houas eds., Caractère Press, Marseille.
- [2] F. Poggi et al. 1999 Turbulence intensity measurements of shock-induced mixing using laser Doppler anemometry, Proceedings of ISSW22, Imperial College, London, July 1999, Ball, Hillier & Roberts eds., CD or book, Imperial College Press.